

C L A I M S

Sub A₆ 1. A table glide adapted for a permanent attachment to a leg of a table comprising:

- (a) a mounting member being secured to a floor contact member;
- (b) the mounting member being adapted to secure the floor contact member to the leg;
- (c) the mounting member including an outer threaded cylinder and a threaded glide mount;
- (d) the mounting member being adapted to cooperate with a securing means on the leg in order to permanently secure the floor contact member to the leg and to form the table glide; and
- (e) the threaded cylinder being adapted to provide a positioning means for the floor contact member.

2. The table glide of Claim 1 further comprising:

- (a) the threaded cylinder being hollow;
- (b) the threaded cylinder having inner threads and outer threads;
- (c) the threaded glide mount having a tamper proof head and a threaded member; and
- (d) the threaded member being adapted to fit into threaded relation with a threaded insert mounted within the table leg.

Sub A7>3.

The table glide of Claim 2 further comprising:

(a) the outer threads being adapted to have male-female relationship with a threaded insert of the securing means;

(b) a threaded aperture receiving the threaded insert at the outer threads thereof; and

(c) the threaded cylinder receiving the threaded member at the inner threads thereof.

4. The table glide of Claim 3 further comprising:

(a) the threaded cylinder having a collar head secured thereto;

(b) the collar head being oppositely disposed from the floor contact member;

(c) the collar head being within an interior of the table leg;

(d) the outer threads providing the positioning by permitted an adjustment of length for the table glide; and

(e) the inner threads securing the floor contact member to the table leg.

Sub A> 11. In table having at least one leg and at least one table glide mounted on the at least one leg; the improvement comprising:

5 (a) the at least one table glide, a mounting member and a floor contact member adapted for a permanent attachment of the at least one table glide to the at least one leg of a table;

(b) the mounting member being secured to the floor contact member;

10 (b) the mounting member being adapted to permanently secure the floor contact member to the leg;

(c) the mounting member including an outer threaded cylinder and a threaded glide mount;

15 (d) the mounting member being adapted to cooperate with a securing means on the leg in order to permanently secure the floor contact member to the leg and to form the table glide; and

20 (e) the threaded cylinder being adapted to provide a positioning means for the floor contact member.

12. The table of Claim 11 further comprising:

- (a) the threaded cylinder being hollow;
- (b) the threaded cylinder having inner threads and outer threads;
- (c) the threaded glide mount having a tamper proof head and a threaded member; and
- (d) the threaded member being adapted to fit into threaded relation with a threaded insert mounted within the table leg.

Sub A9> 13. The table of Claim 12 further comprising:

- (a) the outer threads being adapted to have male-female relationship with a threaded insert of the securing means;
- (b) a threaded aperture receiving the threaded insert at the outer threads thereof; and
- (c) the threaded cylinder receiving the threaded member at the inner threads thereof.

Sub A11>20. The table of Claim 19 further comprising:

(a) the mounting member being adapted to cooperate with a securing means on the leg in order to permanently secure the floor contact member to the leg and to form the table glide; and

(b) the threaded cylinder being adapted to provide a positioning means for the floor contact member.

(c) the positioning means for the floor contact member providing and up and down motion for the floor contact member.